


| Position | Qty. | Description | | | | | | | | | | | | | | |
|-----------------------------|--------------------------------------|---|----------------|----------------------|-----------------------------|-------|----------|-------------------------|-------------------|--------|------------------------|-------|---------------|--------------------------------------|-----------|--------------------------------------|
| | 1 | <p data-bbox="320 338 608 367">Unilift AP35B.50.06.A1.V</p> <div data-bbox="419 389 600 772" style="text-align: center;">  </div> <p data-bbox="711 770 1193 795" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="320 801 587 831">Product No.: 96468356</p> <p data-bbox="320 833 616 862">Submersible effluent pump</p> <p data-bbox="320 891 847 976">Vertical single-stage stainless steel submersible pump with integrated submersible 1-phase motor.</p> <p data-bbox="320 1010 828 1126">The pump is fitted with ring stand and carrying handle and is supplied with a 10 m mains cable and a level switch for automatic start and stop.</p> <p data-bbox="320 1160 810 1274">The impeller is a VORTEX impeller for 35 mm free passage suitable for pumping surface water, groundwater, wastewater and similar.</p> <p data-bbox="320 1308 855 1393">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="320 1426 866 1512">The motor is insulation class F with thermal overload protection and has long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="320 1545 794 1630">The pump has R 2" discharge port and is ready for installation either free-standing or on an auto-coupling system.</p> <p data-bbox="320 1664 405 1693">Liquid:</p> <table data-bbox="320 1695 916 1780"> <tr> <td>Pumped liquid:</td> <td>Any Newtonian liquid</td> </tr> <tr> <td>Maximum liquid temperature:</td> <td>40 °C</td> </tr> <tr> <td>Density:</td> <td>998.2 kg/m³</td> </tr> </table> <p data-bbox="320 1814 443 1843">Technical:</p> <table data-bbox="320 1845 788 1904"> <tr> <td>Type of impeller:</td> <td>VORTEX</td> </tr> <tr> <td>Maximum particle size:</td> <td>35 mm</td> </tr> </table> <p data-bbox="320 1937 437 1966">Materials:</p> <table data-bbox="320 1968 887 2110"> <tr> <td>Pump housing:</td> <td>Stainless steel DIN W.-Nr. 1.4301</td> </tr> <tr> <td>Impeller:</td> <td>Stainless steel DIN W.-Nr. 1.4301</td> </tr> </table> | Pumped liquid: | Any Newtonian liquid | Maximum liquid temperature: | 40 °C | Density: | 998.2 kg/m ³ | Type of impeller: | VORTEX | Maximum particle size: | 35 mm | Pump housing: | Stainless steel DIN W.-Nr. 1.4301 | Impeller: | Stainless steel DIN W.-Nr. 1.4301 |
| Pumped liquid: | Any Newtonian liquid | | | | | | | | | | | | | | | |
| Maximum liquid temperature: | 40 °C | | | | | | | | | | | | | | | |
| Density: | 998.2 kg/m ³ | | | | | | | | | | | | | | | |
| Type of impeller: | VORTEX | | | | | | | | | | | | | | | |
| Maximum particle size: | 35 mm | | | | | | | | | | | | | | | |
| Pump housing: | Stainless steel DIN W.-Nr. 1.4301 | | | | | | | | | | | | | | | |
| Impeller: | Stainless steel DIN W.-Nr. 1.4301 | | | | | | | | | | | | | | | |

| Position | Qty. | Description |
|----------|------|---|
| | | AISI 304 |
| | | <p>Installation:</p> <p>Pump outlet: R 2"</p> <p>Maximum installation depth: 7 m</p> <p>Auto-coupling: Y</p> <p>Electrical data:</p> <p>Type of motor: PSC</p> <p>Power input - P1: 1 kW</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 230 V</p> <p>Rated current: 4.6 A</p> <p>Cos phi - power factor: 0.98</p> <p>Rated speed: 2810 rpm</p> <p>Capacitor size - run: 16 µF/400 V</p> <p>Enclosure class (IEC 34-5): IP68</p> <p>Insulation class (IEC 85): F</p> <p>Length of cable: 10 m</p> <p>Type of cable plug: SCHUKO</p> <p>Others:</p> <p>Net weight: 9.5 kg</p> <p>Gross weight: 11 kg</p> <p>Danish VVS No.: 391270322</p> <p>Swedish RSK No.: 5886038</p> |

| Description | Value |
|-----------------------------|--|
| General information: | |
| Product name: | Unilift AP35B.50.06.A1.V |
| Product No: | 96468356 |
| EAN number: | 5700394943680 |
| Technical: | |
| Max flow: | 5 l/s |
| Head max: | 11 m |
| Type of impeller: | VORTEX |
| Maximum particle size: | 35 mm |
| Materials: | |
| Pump housing: | Stainless steel DIN W.-Nr. 1.4301 AISI 304 |
| Impeller: | Stainless steel DIN W.-Nr. 1.4301 AISI 304 |
| Installation: | |
| Pump outlet: | R 2" |
| Maximum installation depth: | 7 m |
| Inst dry/wet: | S |
| Installation: | horizontal or vertical |
| Auto-coupling: | Y |
| Liquid: | |
| Pumped liquid: | Any Newtonian liquid |
| Maximum liquid temperature: | 40 °C |
| Density: | 998.2 kg/m ³ |
| Electrical data: | |
| Type of motor: | PSC |
| Power input - P1: | 1 kW |
| P2: | 0.66 kW |
| Mains frequency: | 50 Hz |
| Rated voltage: | 1 x 230 V |
| Rated current: | 4.6 A |
| Cos phi - power factor: | 0.98 |
| Rated speed: | 2810 rpm |
| Capacitor size - run: | 16 µF/400 V |
| Enclosure class (IEC 34-5): | IP68 |
| Insulation class (IEC 85): | F |
| Motor protec: | CONTACT |
| Thermal protec: | internal |
| Length of cable: | 10 m |
| Type of cable plug: | SCHUKO |
| Controls: | |
| Level switch: | float switch |
| Others: | |
| Net weight: | 9.5 kg |
| Gross weight: | 11 kg |
| Danish VVS No.: | 391270322 |
| Swedish RSK No.: | 5886038 |

