

Customer	Date	1/15/2019
Contact	Project	
Phone number	Project no.	
Email		

10SV07R030T

Operating data

Pump type	Single head pump	Fluid	Water
No. of pumps / Reserve	1 / 0	Operating temperature t A	°C 4
Nominal flow	m ³ /h 0	pH-value at t A	7
Nominal head	m 0	Density at t A	kg/m ³ 1000
Static head	m 0	Kin. viscosity at t A	mm ² /s 1.569
Inlet pressure	kPa 0	Vapor pressure at t A	kPa 100
Environmental temperature	°C 20	Solids	0
Available system NPSH	m 0	Altitude	m 0

Pump data

Make	Lowara	Nominal	m ³ /h ()
Speed	rpm 2900	Flow	Max- m ³ /h 14
Number of stages	7		Min- m ³ /h
Max. casing pressure	kPa		Nominal m
Max. working pressure	kPa 820.2	Head	at Qmax m 39.6
Head H(Q=0)	m 84		at Qmin m 83.6
Weight	kg 43	Shaft power	kW ()
	Max. mm 96	Max. shaft power	kW 2.5
Impeller R	designed mm 96	Efficiency	%
	Min. mm 96	NPSH 3%	m

Pump Materials

Pump body	Stainless steel / AISI 304
IMPELLER	Stainless steel / AISI 304
DIFFUSER	Stainless steel / AISI 304
Outer sleeve	Stainless steel / AISI 304
SHAFT	Stainless steel / AISI 304
ADAPTER	Cast iron
Base	Aluminium
COUPLING	Aluminium
SEAL HOUSING	Stainless steel / AISI 304
Coupling protection	Stainless steel / AISI 304
Shaft sleeve and bushing	Tungsten carbide
Fill / drain plugs	Stainless steel / AISI 304
Tie rods	Galvanized steel
WEAR RING	Technopolymer PPS

Shaft Seal

e-SV Mechanical seal	Roten
e-SV - Uniten (-30 / +120 °C)	
1 - Rotating part	Silicon Carbide
2 - Stationary part	Resin impregnated carbon
3 - Elastomers	EPDM
4 - Springs	AISI 316
5 - Other components	AISI 316

Motor data

Manufacturer	Lowara	Electric voltage	380 V	Speed	2895 rpm	Insulation class	155 (F)
Specific design	IE3 Three phase surface motor (e-SV)			Frame size	100R	Colour	RAL 5010
Type	PLM100RB14/330 E3 (380-415/660-690V)						
Rated power	3 kW	Degree of protection	IP55				
Electric current	6.29 A						

Remarks:

Customer	Date	1/15/2019
Contact	Project	
Phone number	Project no.	
Email		

10SV07R030T


Hydraulic data

Operating Data Specification		Hydraulic data (duty point)		Impeller design	
Flow	0 m ³ /h	Flow		Impeller R	96 mm
Head	0 m	Head		Frequency	50 Hz
Static head	0 m	MEI >=0,7		Speed	2900 rpm

Power datas referred to:

Water [100%] ; 4°C; 1000kg/m³; 1.57mm²/s


Performance according to ISO 9906:2012 – Grade 3B



Customer	Date	1/15/2019
Contact	Project	
Phone number	Project no.	
Email		

10SV07R030T

Drawing




Dimensions mm

D1	174					Weight
D2	160					42.5
L1	537					kg
L2	298					
L3	537					
L4	323					
L5	537					
L6	547					
M	134					

10SV07R030T

Total lifetime	15	Inflation rate (rate of price increases)	2 %
Annual operating time	5600	Interest rate (for investment)	3 %
Energy cost per kWh	0.00 GBP		
Power input P1			


Total costs



GBP

0%	0.00 GBP	Energy
0%	0.00 GBP	Investment costs
0%	0.00 GBP	Installation & commissioning
0%	0.00 GBP	Operating cost
0%	0.00 GBP	Maintenance & repair
0%	0.00 GBP	Downtime
0%	0.00 GBP	Environmental
0%	0.00 GBP	Decommissioning

First year costs



GBP

0%	0.00 GBP	Energy (1st year)
0%	0.00 GBP	Investment costs (1st year)
0%	0.00 GBP	Installation & commissioning (1st year)
0%	0.00 GBP	Operating cost (1st year)
0%	0.00 GBP	Maintenance & repair (1st year)
0%	0.00 GBP	Downtime (1st year)
0%	0.00 GBP	Environmental (1st year)
0%	0.00 GBP	Decommissioning (1st year)