

For use in potable water or fresh water installations.

The Airfix D expansion vessels operate in such a way that the water flows right through and they are continuously flushed with fresh water from the mains. This prevents tepid, stagnant water from collecting in the vessel in which bacterial growth could occur. Therefore, users can be assured of high quality potable water. Applying an Airfix D expansion vessel to a water heater prevents the opening of the safety group or safety valve each time the potable water is heated. As a result, not only the life of the safety group or safety valve is significantly prolonged (damage or calcification of seat is avoided) but also the risk of permanent leakage (with high water loss as a consequence). An Airfix vessel is also a perfect solution in basement applications where the drain is higher than the safety valve. Airfix D is a flow through vessel, that operates by diverting all of the connection fluid flow, through a special T-piece, into the vessel to prevent stagnation of water in the vessel.

- Full flow through.

Advantages

- The Airfix D is fitted with a synthetic flow through construction and a special T-piece which eliminates the formation of unwanted bacteria inside the vessel.
- Including special brass flow dividing T-piece (3/4") and internal synthetic flow through construction.
- No waste of valuable potable water.
- With special flow through construction.
- Continuous flow through prevents bacterial growth.
- Special butyl rubber diaphragm does not add any colour, odour or taste to the water.
- Corrosion-resistant coating inside, not only on the water side but also on the nitrogen side.
- Internationally approved and certified.
- The clench ring construction allows coating before assembly.
- Nitrogen gas filling for longer retention of pre-charge.
- Airfix D can be fitted with an AirfixControl. AirfixControl enables an easy yearly precharge check of the Airfix expansion vessel.

Technical Specifications

- Full flow through.
- Maximum working pressure: 10 bar.
- Suitable for systems with a maximum system temperature of 120 °C.
- Minimum / maximum temperature diaphragm: 1 °C / 70 °C.
- Vessels in accordance with EN13831.
- Approvals: DVGW-W270
ACS
PZH
KIWA approved execution available on request.
Approved for potable water applications according to CE 2002/16/EC.
- In accordance with Pressure Equipment Directive 2014/68/EU.
- Quality Vignette DIN-DVGW: NW-9481 AU2096.
- Colour: White RAL9010.



Description	Airfix D DHW exp.ves. 12/4,0[10bar]	
Order Code	14349	
GTIN	08712874143494	
Model	<u>Airfix D 8 - 35</u>	
Precharge [bar]	4	
Max. working pressure [bar]	10	
Dimensions	Ø [mm]	286
	H. [mm]	309
Connection	R $\frac{3}{4}$ "	
Weight [kg]	4.3	



Classification General Data

Etim Group	Pressure increase/decrease
Etim Class	Membrane pressure expansion vessel
Product Name	Airfix D DHW exp.ves. 12/4,0[10bar]
Brand	Flamco
Product Type	12

Attributes

Final pressure [bar]	10
For tap water	Yes
Volume [l]	12
Pre-pressure [bar]	4
With fixed wall support	No
Position, vertical	Yes
Max. medium temperature (continuous) [°C]	70
Position, horizontal	No
With legs	No
With exchangeable membrane	No
Nominal inner diameter, expansion connection	3/4 inch (20)
Outer pipe diameter, expansion connection [mm]	26.5
Connection	External thread conical BSPT-R (ISO 7-1 / EN 10226-1)
Colour	White
Diameter [mm]	286
Height [mm]	334

Find more information online:

[Installation and operating instruction](#)

[Declaration of conformity PED 2014/68/EU](#)

[PED Module D](#)

[PED Module D1](#)

[Certificate DIN-DVGW](#)

[Certificate ACS](#)

[Certificate WRAS](#)

[Declaration of conformity UKCA](#)

[Airfix D ADSK](#)

[Airfix D ADSK Revit](#)

[Airfix D DWG](#)

[Airfix D IPT](#)

[Airfix D STEP](#)

[Export catalogue](#)

[White paper Expansion vessels in potable water systems](#)

[Packaging data](#)

[Installation and operating instruction](#)
[Declaration of conformity PED 2014/68/EU](#)
[PED Module D](#)
[PED Module D1](#)
[Certificate DIN-DVGW](#)
[Certificate ACS](#)
[Certificate WRAS](#)
[Declaration of conformity UKCA](#)
[Airfix D ADSK](#)
[Airfix D ADSK Revit](#)
[Airfix D DWG](#)
[Airfix D IPT](#)
[Airfix D STEP](#)
[Export catalogue](#)
[White paper Expansion vessels in potable water systems](#)
[Packaging data](#)
Washway Lane
UK-WA10 6PB, St Helens, Merseyside - gb

T +44 17 447 447 44
E uk.info@aalberts-hfc.com
I flamcogroup.com/uk-en