

For connecting the Flamcomat main or auxiliary vessel to the pump-unit, face sealed female, with ball valve and drainage valve.



Description	Fmat conn. M60-130, D02-130, 1200-5000L		
Order Code	17756		
GTIN	08712874177567		
Model	<u>Flexible Connecting Kit (set of 2)</u>		
Connection	Vessel	G 1 1/2" F	
	Pump-unit	G 1 1/2" M	
Length [mm]	954		
Weight [kg]	5.5		

### Flexible Connecting Kit - Selection Table Flamcomat

Type	Order Code	Flamcomat (G3)		Flamcomat G4		Flamcomat Starter		Flamcomat Starter G4	
		Pump units	Vessels	Pumps units	Vessels	Pumps units	Vessels	Pumps units	Vessels
Flexible connection 1	17610	MM - M80, DM - D80	FG & FB 100 - 1600	all	FG & FB 100 - 1600	all	all	all	all
Flexible connection 2	17611	MM - M80, DM - D80	FG & FB 2000 - 5000	all	FG & FB 2000 - 5000	-	-	-	-
Flexible connection 3	17612	MM - M80, DM - D80	FG & FB 6500 - 10000	all	FG & FB 6500 - 10000	-	-	-	-
Flexible connection 5	17755	M100 - M130, D100 - D130	FG & FB 100 - 1000	-	-	-	-	-	-
Flexible connection 6	17756	M100 - M130, D100 - D130	FG & FB 1200 - 5000	-	-	-	-	-	-
Flexible connection 7	17757	M100 - M130, D100 - D130	FG & FB 6500 - 10000	-	-	-	-	-	-

**Classification General Data**

<b>Etim Group</b>	Hoses and cabinets
<b>Etim Class</b>	Flexible connecting hose (metal)
<b>Product Name</b>	Fmat conn. M60-130, D02-130, 1200-5000L
<b>Brand</b>	FLAMCO
<b>Product Type</b>	Accessories
<b>Artikelnummer</b>	17756
<b>GTIN</b>	08712874177567

**Attributes**

<b>Material</b>	Brass
<b>Inner diameter hose</b>	40 Millimetre
<b>Connection 1</b>	Internal thread
<b>Connection 1 thread size</b>	1 1/2 inch
<b>Nominal diameter connection 1</b>	DN 40
<b>Outer pipe diameter connection 1</b>	48 Millimetre
<b>Connection 2</b>	External thread
<b>Connection 2 thread size</b>	1 1/2 inch
<b>Nominal diameter connection 2</b>	DN 40
<b>Suitable for water</b>	Yes
<b>Suitable for cooled water</b>	Yes
<b>Suitable for oil</b>	No
<b>Max. medium temperature (continuous)</b>	110 Degrees celsius
<b>Max. pressure</b>	6 Bar
<b>With braiding</b>	Yes
<b>With sealing rings/gaskets</b>	No
<b>Length</b>	954 Millimetre

**Find more information online:**[Flexible connections 1, 2, 3](#)[Flexible connections 5, 6, 7](#)[Export catalogue](#)[Packaging data](#)

Washway Lane  
UK-WA10 6PB, St Helens, Merseyside - gb

T +44 17 447 447 44  
E [uk.info@aalberts-hfc.com](mailto:uk.info@aalberts-hfc.com)  
I [flamcogroup.com/uk-en](http://flamcogroup.com/uk-en)