

Vapour-tight insulation for use in cooling water installations.

Technical Specifications

- Fire category B1 according to DIN 4102.
- λ - value according to DIN EN 12667:
0.031 W/(m.K) at -20 °C
0.035 W/(m.K) at +20 °C
- Temperature range (min./max.): -200 °C / +105 °C.
- Diffusion resistance according to EN 12086 (DIN 52615): $\mu = 10000$.
- Thickness: 25 mm (if used as insulation).
- Corrosion risk according to DIN 1988/7: pH neutral.



Description	FlexTherm InsulationPS-K 2000L
Order Code	18274
GTIN	08712874182745
Model	<u>25mm Vapour-tight insulation mantle</u>
Colour	black

Classification General Data

Etim Group	Boilers and heaters
Etim Class	Accessories/spare parts for boilers
Product Name	FlexTherm InsulationPS-K 2000L
Brand	Flamco
Product Type	2000
Artikelnummer	18274

Attributes

Accessories for storage tank boiler	Coat (expired)
Accessory	No
Spare part	No

Find more information online:

- [Installation and operating instruction](#)
- [Export catalogue](#)
- [Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com