





CS 40

STANDARDISED - CAST IRON







DIMENSIONS (mm)				
DN	DE	K	HOLES	
			QTY	Ø
40	150	110	4	18
65	185	145	4	18

item code	model (3PH 230v-400v)	output (kW)	flow (l/min)	head (mtrs)	DNM	DNA	A	B	C	D	E	F	G	H	H1	H2	N	O	P	weight (kgs)
19-15-1282	CS 40-160 B	3	900	32	40	65	100	70	550	240	190	15	240	322	132	160	80	15	50	47
19-15-1087	CS 40-160 A	4	970	34	40	65	100	70	550	240	190	15	240	322	132	160	80	15	50	50
19-15-1252	CS 40-200 B	5.5	1200	46	40	65	100	70	640	265	212	15	281	370	160	180	100	15	50	65
19-15-1094	CS 40-200 A	7.5	1230	57	40	65	100	70	640	265	212	15	281	370	160	180	100	15	50	71
19-15-1247	CS 40-250 B	11	1000	72	40	65	125	95	745	320	250	15	335	435	180	225	100	18	65	91
19-15-1171	CS 40-250 A	15	1050	90	40	65	125	95	745	320	250	15	335	435	180	225	100	18	65	121

PREMIUM EFFICIENCY MOTORS (IE3) AVAILABLE FOR ALL MODELS (P.O.A.)

CS 50

STANDARDISED - CAST IRON



DIMENSIONS (mm)				
DN	DE	K	HOLES	
			QTY	Ø
50	165	125	4	18
65	185	145	4	18

item code	model (3PH 230v-400v)	output (kW)	flow (l/min)	head (mtrs)	DNM	DNA	A	B	C	D	E	F	G	H	H1	H2	N	O	P	weight (kgs)
19-15-1221	CS 50-160 D	3	1200	25	50	65	100	70	570	265	212	15	268	372	160	180	100	15	50	50
19-15-1066	CS 50-160 C	4	1000	30	50	65	100	70	570	265	212	15	268	372	160	180	100	15	50	60
19-15-1011	CS 50-160 B	5.5	1600	37	50	65	100	70	650	265	212	15	268	372	160	180	100	15	50	65
19-15-1098	CS 50-160 A	7.5	1600	40	50	65	100	70	650	265	212	15	268	372	160	180	100	15	50	71
19-15-1129	CS 50-200 C	9.2	1500	48	50	65	100	70	745	265	212	15	335	425	160	200	100	18	50	82
19-15-1054	CS 50-200 B	11	1500	52	50	65	100	70	745	265	212	15	335	425	160	200	100	18	50	89
19-15-1251	CS 50-200 A	15	1500	65	50	65	100	70	745	265	212	15	335	425	160	200	100	18	50	122
19-15-1073	CS 50-250 C	15	1400	70	50	65	125	95	750	320	250	15	340	435	180	225	100	18	65	125
19-15-1016	CS 50-250 B	18.5	1400	80	50	65	125	95	795	320	250	15	340	435	180	225	100	18	65	140
19-15-1256	CS 50-250 A	22.5	1400	90	50	65	125	95	825	320	250	15	360	455	180	225	100	18	65	149

PREMIUM EFFICIENCY MOTORS (IE3) AVAILABLE FOR ALL MODELS (P.O.A.)