

Qty. Description

1 SP 95-10



Note! Product picture may differ from actual product

Product No.: [19004310](#)

Submersible borehole pump, suitable for pumping clean water. Can be installed vertically or horizontally. All steel components are made in stainless steel, EN 1.4301 (AISI 304), that ensures high corrosive resistance. This pump carries drinking water approval.

The pump is fitted with a 45 kW MMS8000 motor with sand shield, water-lubricated journal bearings and a volume compensating diaphragm.

The rewindable motor construction allows complete access to the windings for easy rewinding.

The stator windings are PE/PA insulated made for continuous operations (S1).

Suitable for temperatures up to 50 °C.

The motor is fitted with a mechanical shaft seal.

The motor is not fitted with a temperature sensor. If temperature monitoring is desired, a Pt100 or Pt1000 sensor can be fitted.

The motor is for direct-on-line starting (DOL).

Liquid:

| | |
|------------------------------|-------------------------|
| Pumped liquid: | Water |
| Liquid max temp: | 45 °C |
| Max liquid t at 0.15 m/sec: | 40 °C |
| Max liquid t at 0.5 m/sec: | 45 °C |
| Selected liquid temperature: | 20 °C |
| Density: | 998.2 kg/m ³ |

Technical:

| | |
|--|----------------------|
| Pump speed on which pump data are based: | 2900 rpm |
| Rated flow: | 95 m ³ /h |
| Rated head: | 121 m |
| Shaft seal for motor: | SIC/SIC |
| Curve tolerance: | ISO9906:2012 3B |
| Motor version: | T45 |

Materials:

| | |
|-----------|--|
| Pump: | Stainless steel EN 1.4301 AISI 304 |
| Impeller: | Stainless steel EN 1.4301 AISI 304 |
| Motor: | Cast iron DIN W.-Nr. 0.6025 ASTM 35-40 |

Installation:

| | |
|-----------------|--------|
| Pump outlet: | RP5 |
| Motor diameter: | 8 inch |

Electrical data:



Company name:

Created by:

Phone:

Date:

08/08/2022

Qty. Description

| | | |
|---|----------------------------------|----------------------|
| 1 | Motor type: | MMS8000 |
| | Rated power - P2: | 45 kW |
| | Power (P2) required by pump: | 45 kW |
| | Mains frequency: | 50 Hz |
| | Rated voltage: | 3 x 380-400-415 V |
| | Rated current: | 95.5-96.5-96.0 A |
| | Starting current: | 560-600-680 % |
| | Cos phi - power factor: | 0.88-0.82-0.80 |
| | Rated speed: | 2900-2910-2920 rpm |
| | Start. method: | direct-on-line |
| | Enclosure class (IEC 34-5): | IP68 |
| | Built-in temp. transmitter: | no |
| | Motor No: | 96476891 |
| | Windings: | PE2/PA |
| | Others: | |
| | Minimum efficiency index, MEI ≥: | -.-- |
| | ErP status: | EuP Standalone/Prod. |
| | Net weight: | 244 kg |
| | Gross weight: | 296 kg |
| | Shipping volume: | 0.475 m ³ |
| | Country of origin: | GB |
| | Custom tariff no.: | 84137029 |