

Data sheet

Hydraulic data

Minimum efficiency index (MEI)	0,4
Max. operating pressure p	10 bar
Maximum operating pressure PN	10 bar
Min. fluid temperature T_{\min}	-20 °C
Max. fluid temperature T_{\max}	120 °C
Max. ambient temperature T_{\max}	40 °C
Flow max Q_{\max}	133,5 m ³ /h
Flow opt Q_{opt}	76,4 m ³ /h
Head max H_{\max}	5,0 m
Head opt H_{opt}	3,6 m
Head $H_{Q_{\min}}$	5,0 m
Head H_{20}	5,0
Head H_{40}	4,7
Head H_{60}	4,2
Head H_{80}	3,4
Head H_{100}	2,5
Head H_{120}	1,6

Motor data

Mains connection	3~400 V, 50 Hz
Voltage tolerance	±10 %
Rated power P_2	1,1 kW
Rated current I_N	2,25 A
Rated speed n	1450 1/min
Power factor $\cos \varphi$	0,83
Motor efficiency η_M 50%	83,3 Percentage
Motor efficiency η_M 75%	84,7 Percentage
Motor efficiency η_M 100%	84,1 Percentage
Motor winding up to 3 kW	-
Motor winding from 4 kW	-
Insulation class	F
Protection class motor	IP55
Integrated full motor protection	-

Materials

Pump housing	Cast iron
Impeller	Cast iron
Shaft	Stainless steel
Mechanical seal	AQ1EGG
Lantern	Cast iron

Installation dimensions

Pipe connection on the suction side DN_s	DN 100
Pipe connection on the pressure side DN_d	DN 100
Port-to-port length L_0	500 mm