

Data sheet

Hydraulic data

Minimum efficiency index (MEI)	0,4
Max. operating pressure p	10 bar
Maximum operating pressure PN	10 bar
Min. fluid temperature T_{\min}	-20 °C
Max. fluid temperature T_{\max}	120 °C
Max. ambient temperature T_{\max}	40 °C
Flow max Q_{\max}	197,7 m ³ /h
Flow opt Q_{opt}	114,8 m ³ /h
Head max H_{\max}	9,3 m
Head opt H_{opt}	7,4 m
Head $H_{Q_{\min}}$	9,3 m
Head H_{20}	9,3
Head H_{40}	9,3
Head H_{60}	9,0
Head H_{80}	8,6
Head H_{100}	8,0
Head H_{120}	7,1

Motor data

Mains connection	3~400 V, 50 Hz
Voltage tolerance	±10 %
Rated power P_2	3 kW
Rated current I_N	6 A
Rated speed n	1450 1/min
Power factor $\cos \varphi$	0,82
Motor efficiency η_M 50%	87 Percentage
Motor efficiency η_M 75%	88,2 Percentage
Motor efficiency η_M 100%	87,7 Percentage
Motor winding up to 3 kW	-
Motor winding from 4 kW	-
Insulation class	F
Protection class motor	IP55
Integrated full motor protection	-

Materials

Pump housing	Cast iron
Impeller	Cast iron
Shaft	Stainless steel
Mechanical seal	AQ1EGG
Lantern	Cast iron

Installation dimensions

Pipe connection on the suction side DN_s	DN 100
Pipe connection on the pressure side DN_d	DN 100
Port-to-port length L_0	500 mm