

A Flexcon KSG boiler connection assembly is suitable for venting and safeguarding sealed heating or cooling systems including those with glycol-based additives (maximum 50%).

### Advantages

- The Flexcon KSG boiler connection assembly inclusive of EPP insulation.
- With a Flexvent automatic air vent, with valve sleeve, Flamco safety valve, pressure gauge with valve sleeve.

### Technical Specifications

- Minimum/Maximum working temperature: -10 °C / 90 °C.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- Safety valve: ½" x ¾", 2.5 bar (110 kW).
- Flexvent ¾" with shut-off valve.
- Pressure gauge: Ø 61 mm, 6.0 bar with shut-off valve.
- Insulation: material EPP - color: black.



Description	Flexcon KSG 3/4" 2,5bar EcoPlus
Order Code	27930
GTIN	08712874279308
Model	<u>Flexcon KSG EcoPlus</u>
Set pressure [bar]	2.5
Connection	Rp ¾"
Heating capacity [kW]	110



### Classification General Data

Etim Group

Etim Class

Product Name Flexcon KSG Rp¾" 2.5bar EcoPlus

Brand Flamco

Product Type Flexcon KSG 3/4" 2,5bar EcoPlus

Artikelnummer 27930

**Find more information online:**

[Installation and operating instruction](#)

[Flexcon KSG EcoPlus DWG](#)

[Flexcon KSG EcoPlus STEP](#)

[Flexcon KSG EcoPlus RFA](#)

[Export catalogue](#)

[Packaging data](#)

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 (0)36 52 62 300  
E [info@aalberts-hfc.com](mailto:info@aalberts-hfc.com)  
I [flamcogroup.com](http://flamcogroup.com)