

The compact, proven design has high efficiency and guaranteed operation for heating and air conditioning.
The water within the installation contains air which can form corrosion and reduce the thermal transfer. A Flexvent is fitted at places where the air collects.

Advantages

- Most types are equipped with a shut-off valve for easy fitting and dismantling.
- A Flexvent float vent is easy to fit in any installation due to its very small dimensions.
- The relatively large air cushion at the top of each type of Flexvent float vent protects the valve seat sufficiently against contamination, so that the Flexvent will not leak.
- To guarantee top quality, we test all Flexvents before they leave our facility!

Technical Specifications

- Minimum/Maximum working temperature: -10 °C / 120 °C.
- Minimum/Maximum working pressure: 0.2 / 10.0 bar.
- Suitable for addition of glycol-based anti-freeze up to 50%.



Description	Flexvent Top Rp 1/2"	
Order Code	28515	
GTIN	08712874285156	
Model	Flexvent Top	
Dimensions	Ø [mm]	54
	H. [mm]	86
Connection	Rp 1/2"	
Shut-off valve	no	



Classification General Data

Etim Group	Measuring and control devices
Etim Class	De-aerator (automatic)
Product Name	Flexvent Top Rp½"
Brand	Flamco
Product Type	1/2
Artikelnummer	28515

Attributes

Material valve	Other
Material float	Other
Outer pipe diameter	21.3 Millimetre
Maximum pressure at 20 °C	10 Bar
Max. operating pressure at 20 °C	10 Bar
Flange compression class	PN 10
Max. medium temperature (continuous)	120 Degrees celsius
Height	87.3 Millimetre
Working length connection 1	12.4 Millimetre
Lockable	No

Find more information online:

[Installation and operating instruction](#)
[Statement of Conformity](#)
[Flexvent Top DWG](#)
[Flexvent Top STEP](#)
[Flexvent Top 1-2 ADSK](#)
[Flexvent Top White 3-8 RFA](#)
[Export catalogue](#)
[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com