

## Product Data Sheet (2021-06-08)

## 31053 - Flamcovent Clean Smart 500 F





| Description                        |        | Flamcovent Clean Smart F DN500      |
|------------------------------------|--------|-------------------------------------|
| Article                            |        | 31053                               |
| Model                              |        | Flamcovent Clean Smart F - 10.0 bar |
| Capacity [I]                       |        | 1768                                |
| Connection                         | [DN]   | 500                                 |
|                                    | [mm]   | 508.0                               |
| Dimensions                         | A [mm] | 2628                                |
|                                    | B [mm] | 1580                                |
|                                    | C [mm] | 1470                                |
|                                    | D [mm] | 1000                                |
| $K_v * [m^3/h] (\Delta P = 1 bar)$ |        | 8387                                |
| Weight [kg]                        |        | 745                                 |



## **Classification General Data**

| Etim Group   | Filters/separators                                        |
|--------------|-----------------------------------------------------------|
| Etim Class   | Air-/dirt separator for central<br>heating/cooling system |
| Product Name | Flamcovent Clean Smart F DN500                            |
| Brand        | Flamco                                                    |
| Product Type | 500                                                       |

## **Attributes**

| Separator type                            | Air/dirt  |
|-------------------------------------------|-----------|
| Suitable for heating                      | Yes       |
| Suitable for cooling                      | Yes       |
| Nominal diameter                          | DN 500    |
| Outer pipe diameter [mm]                  | 508       |
| Connection                                | Flange    |
| Construction length [mm]                  | 1580      |
| Article compression class                 | PN 10     |
| Surface protection                        | Untreated |
| Operating principle                       | Other     |
| Flow-through capacity [m <sup>3</sup> /h] | 0 - 2189  |
| Suitable for open system                  | No        |
| With blow-off valve                       | Yes       |
| Suitable for closed system                | Yes       |
| With dismountable filter                  | No        |
| Filter volume [I]                         | 1768      |
| Filter mesh density [mm]                  | 0         |
| With automatic de-aerator                 | Yes       |
| With integrated replenishment automat     | No        |
| With couplers                             | No        |
| Inlet/outlet offset distance [mm]         | 0         |

Flamco Group Plotterweg 31 3821 BB, Amersfoort - nl **T** +31 33 299 75 00 **E** <u>info@flamcogroup.com</u> I flamcogroup.com