Reflex Refix DE 33 st, diaphragm expansion vessel without through flow, blue, 10/4 bar

Article number: 7305500





Features

Туре	DE 33 st
Colour	blue
Diaphragm material	butyl
Nominal volume	33 I
Max. useful volume	23 I
Max. permissible system temperature	70 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	10 bar
Factory provided gas supply pressure	4 bar
Connection	G 3/4"
Diameter	354 mm
Height	520 mm
High water connection	66 mm
Tilt dimension approx.	529 mm
Weight	5,70 kg

Description

Refix DE

Non-flowed through diaphragm expansion tank for water supply installations that are not subject to DIN 1988, e.g. fire extinguishing and service water systems, underfloor heating or heat source installations. Vessels fitted according to DIN EN 13831. Approval according to Pressure Equipment Directive 2014/68/EC.

- Bladder according to DIN EN 13831 / replaceable from 50 litres
- For antifreeze additive of at least 25 50 %
- Parts in contact with water are corrosion-protected
- Durable epoxy resin coating
- 33 litres with brackets, from 50 litres with adjustable feets
- following types incl. pressure gauge:
 - \rightarrow 10/16 bar: from Ø 1.000 mm
 - \rightarrow 25 bar: from Ø 450 mm
- Pressure gauge and supply pressure valve protected by clip

Note:

No licence requirement according to SWKI HE301-01 and SVTI for (PSV * VN \leq 3,000 bar * litre).

