

JE 2-120 G10 NT20

Electric - Qmax 44 m³/h (193 USgpm) - Hmax 20 m (65 ft)

Code 8381063389



Indicative picture of the product

Product Data

Suction port
Threaded - 2" ISO 228 (BSP)

Delivery port
Threaded - 2" ISO 228 (BSP)

Qmax
44 m³/h - 733 l/min (193 USgpm)

Hmax
20 m (65 ft)

Solids handling
25 mm (1")

Motor power
2,2 kW – 3 HP

Motor type
IEC standard

Winding for inverters
Cast iron casing

Motor brand
WEG W22 Premium

Weight
57 kg (126 lb)

Close-coupled self-priming centrifugal pump with electric motor

Characteristics

The J series self-priming centrifugal pumps are used in applications where a rapid priming capacity is required from demanding suction heights combined with the ability to transfer and manage polluted fluids, dirty and abrasives with suspended large diameter solids. The system is based on an inspectable pump casing which also acts as a water tank allowing a first quick priming without auxiliary systems, simplifying management of the system and reducing the time for maintenance. Within the physically permitted suction height limits, J pumps are a more comfortable and reliable solution than submersible pumps and vertical submersed impeller pumps.

Benefits

- 1)Rapid self-priming**
Without foot valve up to a height of 7.5 m (24.5 ft)
- 2)High resistance**
To abrasive liquids which are turbid and sandy
- 3)Semi-open impeller**
High thickness casting impact resistant
- 4)Wear plate**
Easily replaceable cast iron wear plate, front to the impeller
- 5)Easy maintenance**
Removable front cover for direct access to the impeller

Applications

Industry:

clean, dirty, sandy, muddy, neutral, alkaline, acidic liquids; low viscous petroleum products, solvents even if dirty; milk of lime, caustic soda; washing, cooling, recirculation, smoke scrubbing.

Treatment:

pumping polluted corrosive wastewater containing sand, mud or solids in suspension; dosing neutralizing liquids; pumping out settled sludge.

Naval:

loading and unloading; bilge pumping; washing, fire-fighting, stripping, sanitary duty and circulation.

Agriculture:

surface irrigation; liquid manure oxygenation; transfer and spraying liquid manure or fertilizers; distribution of liquid animal feed; transfer of wine must; washing.

Varisco S.r.l. has certified its Quality, Environment and Safety Management System in accordance with the requirements of the international standard ISO 9001-14001-45001, recognized by the Lloyd Register.

JE 2-120 G10 NT20

PERFORMANCE CURVES

Test according to **UNI EN ISO 9906 standard - level 2B**

Test liquid: **clean water, density 1.000 kg/m³**


Spherical solids handling: **D.25 mm (1")**

Priming time (2900 rpm): **26s from 1,5 m (5 ft)**


Installed power: **2,2 kW - 3 HP (2.900 rpm)**

Noise Curve


dB(A)=max noise level at 1 m



Multiple Speed Curve



NPSHr Curve



JE 2-120 G10 NT20

TECHNICAL DATA

Pump

Pump model	J 2-120 G10
Qmax [2.900 rpm]	44 m³/h – 733 l/min (193 Usgpm)
Hmax [2.900 rpm]	20 m (65 ft)
Suction port	threaded – 2" ISO 228 (BSP)
Delivery port	threaded – 2" ISO 228 (BSP)
Impeller type	semi-open, 3 vane
Solids handling	25 mm (1")
Casing	EN 1561 EN-GJL-200 cast iron
Impeller	EN 1561 EN-GJL-200 cast iron
Wear plate	EN 1561 EN-GJL-200 cast iron
Non-return valve	check-valve, NBR
Shaft	C45E EN 10083-2 steel
Mechanical seal	Silicon carbide / Silicon carbide
Elastomers	NBR
Lubrication	Grease

Motor

Supply electric (Type three-phase)	220 VD/380 VY + - 5%	230 VD/400 VY + - 10%	240 VD/415 VY + - 5%
Frequency		50 Hz + - 3% / 2.900 rpm	
Power consumption	7,91/4,58 A	7,75/4,45 A	7,56/4,37 A
Inrush current Is/In	7.1	7.5	8
Max efficiency (100%)	85,9% (IE3)	85,9% (IE3)	86,5% (IE3)
Brand		WEG W22 Premium	
Construction standard		IEC 60034-1	
Construction		Cast iron, TEFC	
Constructive form		IM 2101 B34	
No. poles		2	
Rated power		2,2 kW - 3 HP	
Protection rating		IP55	
Marking		CE, UL, CSA, EAC	
Insulation class/Temperature		F/80°K	
Service type		Continuous - S1 Variable - suitable for inverter use (30-50 Hz)	
Temperature sensors		PTC, available as optional	

Arrangement

Model	Close-coupled N
Dimensions	190 x 596 x 291 mm (7.5 x 23.5 x 11.5 ")
Coatings	bicomponent, average thickness of 100 µm
Color	RAL 5010 blue (standard)
Features	close-coupled with rigid coupling "N"
Height connection	0,2 m (0.7 ft)

Optionals

Flanged ports DN50 PN16 EN1092-2 Type B	cod. 10042783
Flanged ports 2" ANSI B16.1 Class 125 R.F.	cod. 10042818
Automatic mechanical seal greaser	cod. 10008316
Integrated VSD motor inverter	N/A


Weight

Net weight	57 kg (126 lb)
------------	----------------


JE 2-120 G10 NT20

DIMENSIONS

mm [in]



FLANGIATURA SU RICHIESTA / FLANGES ON REQUEST



PACKAGING DIMENSIONS

Dimensions

JE 2-120 G10 NT20 (L x P x H mm)

720 x 270 x 480 + BOX

Gross weight (pump + packing)

61 Kg

