


Position	Qty.	Description
	1	<p data-bbox="320 338 550 367">Unilift AP12.40.08.1</p> <div data-bbox="403 400 619 779" style="text-align: center;">  </div> <p data-bbox="711 770 1193 795" style="text-align: right;">Note! Product picture may differ from actual product</p> <p data-bbox="320 801 686 862">Product No.: 96001873 Submersible drainage pump type</p> <p data-bbox="320 891 849 1066">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase totally enclosed motor in insulation class F with thermal overload protection. The pump is fitted with a suction strainer.</p> <p data-bbox="320 1099 794 1216">The impeller is a SEMI OPEN impeller for 12 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p data-bbox="320 1249 829 1337">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="320 1370 842 1487">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="320 1520 817 1695">The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="320 1729 917 1845">Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m³</p> <p data-bbox="320 1879 821 1966">Technical: Type of impeller: SEMI OPEN Maximum particle size: 12 mm</p> <p data-bbox="320 2000 885 2116">Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p>

Position	Qty.	Description
		<p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Pump outlet: Rp 1 1/2 Maximum installation depth: 7 m</p> <p>Electrical data: Type of motor: PSC Power input - P1: 1.3 kW Mains frequency: 50 Hz Rated voltage: 1 x 230 V Rated current: 5.9 A Cos phi - power factor: 0,99 Rated speed: 2780 rpm Capacitor size - run: 16 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE</p> <p>Others: Net weight: 12 kg Gross weight: 13 kg</p>

Description	Value
General information:	
Product name:	Unilift AP12.40.08.1
Product No:	96001873
EAN number:	5700390897246
Technical:	
Max flow:	5.83 l/s
Head max:	15 m
Type of impeller:	SEMI OPEN
Maximum particle size:	12 mm
Materials:	
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Installation:	
Pump outlet:	Rp 1 1/2
Maximum installation depth:	7 m
Inst dry/wet:	D/S
Installation:	horizontal or vertical
Liquid:	
Pumped liquid:	Any Newtonian liquid
Liquid temperature range:	0 .. 55 °C
Density:	998.2 kg/m ³
Electrical data:	
Type of motor:	PSC
Power input - P1:	1.3 kW
P2:	0.8 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	5.9 A
Cos phi - power factor:	0,99
Rated speed:	2780 rpm
Capacitor size - run:	16 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	10 m
Type of cable plug:	NONE
Others:	
Net weight:	12 kg
Gross weight:	13 kg

