

Position	Qty.	Description
1	Unilift AP50.50.11.A1.V	 <p>Note! Product picture may differ from actual product</p> <p>Product No.: 96404186 Submersible drainage pump type</p> <p>Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase totally enclosed motor in insulation class F with thermal overload protection.</p> <p>The pump is fitted with suction strainer and level switch for automatic start and stop.</p> <p>The impeller is a VORTEX impeller for 50 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p>The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p>The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p>The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p>Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m³</p> <p>Technical: Type of impeller: VORTEX Maximum particle size: 50 mm</p> <p>Materials: Pump housing: Stainless steel</p>



Company name:
Created by:
Phone:

Date: 27/02/2018

Position	Qty.	Description
		<p>Impeller: DIN W.-Nr. 1.4301 AISI 304 Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Pump outlet: Rp 2 Maximum installation depth: 7 m</p> <p>Electrical data: Type of motor: PSC Power input - P1: 1.6 kW Mains frequency: 50 Hz Rated voltage: 1 x 230 V Rated current: 8 A Cos phi - power factor: 0,92 Rated speed: 2800 rpm Capacitor size - run: 20 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE</p> <p>Others: Net weight: 15.9 kg Gross weight: 16.7 kg</p>



Company name:

Created by:

Phone:

Date:

27/02/2018

Description	Value
General information:	
Product name:	Unilift AP50.50.11.A1.V
Product No:	96404186
EAN number:	5700390910440
Technical:	
Max flow:	8.33 l/s
Head max:	12 m
Type of impeller:	VORTEX
Maximum particle size:	50 mm
Materials:	
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Installation:	
Pump outlet:	Rp 2
Maximum installation depth:	7 m
Inst dry/wet:	D/S
Installation:	horizontal or vertical
Liquid:	
Pumped liquid:	Any Newtonian liquid
Liquid temperature range:	0 .. 55 °C
Density:	998.2 kg/m ³
Electrical data:	
Type of motor:	PSC
Power input - P1:	1.6 kW
P2:	1.1 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	8 A
Cos phi - power factor:	0,92
Rated speed:	2800 rpm
Capacitor size - run:	20 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	10 m
Type of cable plug:	NONE
Controls:	
Level switch:	float switch
Others:	
Net weight:	15.9 kg
Gross weight:	16.7 kg

