

Company name: Created by: Phone:

**Date:** 08/08/2022

Qty. | Description

1 SQE 2-100



Note! Product picture may differ from actual product

Product No.: 96510154

3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.

The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.

The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.

The motor is fitted with a replaceable end cover with socket.

Liquid:

Pumped liquid: Water
Liquid temperature range: 0 .. 35 °C
Selected liquid temperature: 20 °C
Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 10700 rpm

Rated flow: 2 m³/h Rated head: 108 m

Approvals: CE,PCBC,RCM,EAC,CN Rohs Exempt,Morocco,UKCA,SEPRO

Curve tolerance: ISO9906:2012 3B

Materials:

Pump: Stainless steel

EN 1.4301 AISI 304

Impeller: Composite

ZYTEL 70G30 HSLR PA6.6-GF30

Motor: Stainless steel

DIN W.-Nr. 1.4301

**AISI 304** 

Installation:

Maximum operating pressure: 15 bar Pump outlet: Rp1 1/4 Minimum borehole diameter: 76 mm

Electrical data:

Motor type: MSE3
Power input - P1: 2.05 kW
Rated power - P2: 1.55 kW
Power input P3: 1.35 kW
Mains frequency: 50 Hz
Rated voltage: 1 x 200-240 V



Company name: Created by: Phone:

**Date:** 08/08/2022

## Qty. | Description

Rated current: 11.2 A
Power factor: 1.00
Rated speed: 10700 rpm
Start. method: direct-on-line

Enclosure class (IEC 34-5): IP68
Insulation class (IEC 85): F
Length of cable: 1.5 m
Motor No: 96160856

Others:

Net weight: 5.84 kg Gross weight: 6.57 kg Shipping volume: 0.01 m<sup>3</sup> Danish VVS No.: 388442500 Swedish RSK No.: 5853373 Finnish LVI No.: 4762533 Norwegian NRF no.: 9041354 Country of origin: DE Custom tariff no.: 84137029