

Qty. Description

1 DPI---0-10b/1/ G/D.900-B/V-5/-B/02B/SD-1



Note! Product picture may differ from actual product

Product No.: [96611550](#)

The transmitter is made of 1.4404 stainless steel.

Liquid:
Liquid temperature range: -10 .. 70 °CTechnical:
Approvals: EAC
Pressure differential functionality = Yes/No: Y
Pressure relative functionality (Yes/No): N
Flow functionality (Yes/No): N
Temperature functionality (Yes/No): N
Minimum measuring pressure: 0 bar
Maximum measuring pressure: 10 barInstallation:
Range of ambient temperature: -40 .. 70 °CElectrical data:
Enclosure class (IEC 34-5): IP55
Length of cable: 0.9 m
Minimum rated voltage dc: 12.00 V
Maximum rated voltage dc: 30.00 VOthers:
Danish VVS No.: 475273100
Finnish LVI No.: 4534508

Description	Value
General information:	
Product name:	DPI/---0-10b/1/ G/D.900-B/V-5/-B/02B/SD-1
Product No:	96611550
EAN number:	5700834481901
Technical:	
Approvals:	EAC
Pressure differential functionality = Yes/No:	Y
Pressure relative functionality (Yes/No):	N
Flow functionality (Yes/No):	N
Temperature functionality (Yes/No):	N
Minimum measuring pressure:	0 bar
Maximum measuring pressure:	10 bar
Installation:	
Range of ambient temperature:	-40 .. 70 °C
Liquid:	
Liquid temperature range:	-10 .. 70 °C
Electrical data:	
Enclosure class (IEC 34-5):	IP55
Length of cable:	0.9 m
Minimum rated voltage dc:	12.00 V
Maximum rated voltage dc:	30.00 V
Others:	
Danish VVS No.:	475273100
Finnish LVI No.:	4534508



