

Qty. Description

1 DPI/---0-10b/2/ F/M2.00-X/EG6/-B/02B/SD-1



Note! Product picture may differ from actual product

Product No.: [97747208](#)

The transmitter is made of 1.4404 stainless steel.

Liquid:

Liquid temperature range: -30 .. 120 °C

Technical:

Approvals: EAC
Approvals for drinking water: WRAS, ACS
Pressure differential functionality = Yes/No: Y
Pressure relative functionality (Yes/No): N
Flow functionality (Yes/No): N
Temperature functionality (Yes/No): Y
Minimum measuring pressure: 0 bar
Maximum measuring pressure: 10 bar
Minimum measuring temperature: 0 °C
Maximum measuring temperature: 100 °C

Installation:

Range of ambient temperature: -25 .. 60 °C

Electrical data:

Enclosure class (IEC 34-5): IP67
Length of cable: 2 m
Minimum rated voltage dc: 16.60 V
Maximum rated voltage dc: 30.00 V

Others:

Danish VVS No.: 475274300



Company name:

Created by:

Phone:

Date:

30/12/2022

Description	Value
General information:	
Product name:	DPI/---0-10b/2/ F/M2.00-X/EG6/-B/02B/SD-1
Product No:	97747208
EAN number:	5710623682884
Technical:	
Approvals:	EAC
Approvals for drinking water:	WRAS, ACS
Pressure differential functionality = Yes/No:	Y
Pressure relative functionality (Yes/No):	N
Flow functionality (Yes/No):	N
Temperature functionality (Yes/No):	Y
Minimum measuring pressure:	0 bar
Maximum measuring pressure:	10 bar
Minimum measuring temperature:	0 °C
Maximum measuring temperature:	100 °C
Installation:	
Range of ambient temperature:	-25 .. 60 °C
Liquid:	
Liquid temperature range:	-30 .. 120 °C
Electrical data:	
Enclosure class (IEC 34-5):	IP67
Length of cable:	2 m
Minimum rated voltage dc:	16.60 V
Maximum rated voltage dc:	30.00 V
Others:	
Danish VVS No.:	475274300

