

Qty. Description

1 DPI---0-10b/2/ C/M2.00-X/VG6/-B/02B/SD-1



Note! Product picture may differ from actual product

Product No.: [97747242](#)

The transmitter is made of 1.4404 stainless steel.

Liquid:

Liquid temperature range: -30 .. 120 °C

Technical:

Approvals: EAC

Pressure differential functionality = Yes/No: Y

Pressure relative functionality (Yes/No): N

Flow functionality (Yes/No): N

Temperature functionality (Yes/No): N

Minimum measuring pressure: 0 bar

Maximum measuring pressure: 10 bar

Installation:

Range of ambient temperature: -25 .. 60 °C

Electrical data:

Enclosure class (IEC 34-5): IP67

Length of cable: 2 m

Minimum rated voltage dc: 12.50 V

Maximum rated voltage dc: 30.00 V

Others:

Danish VVS No.: 475274500



Company name:

Created by:

Phone:

Date:

30/12/2022

| Description | Value |
|--|--|
| General information: | |
| Product name: | DPI/---0-10b/2/ C/M2.00-X/VG6/-B/02B/SD-1 |
| Product No: | 97747242 |
| EAN number: | 5710623683188 |
| Technical: | |
| Approvals: | EAC |
| Pressure differential functionality = Yes/No: | Y |
| Pressure relative functionality (Yes/No): | N |
| Flow functionality (Yes/No): | N |
| Temperature functionality (Yes/No): | N |
| Minimum measuring pressure: | 0 bar |
| Maximum measuring pressure: | 10 bar |
| Installation: | |
| Range of ambient temperature: | -25 .. 60 °C |
| Liquid: | |
| Liquid temperature range: | -30 .. 120 °C |
| Electrical data: | |
| Enclosure class (IEC 34-5): | IP67 |
| Length of cable: | 2 m |
| Minimum rated voltage dc: | 12.50 V |
| Maximum rated voltage dc: | 30.00 V |
| Others: | |
| Danish VVS No.: | 475274500 |

