

Company name: Created by: Phone:

**Date:** 30/12/2022

Qty. | Description

DPI/---0-16b/2/ C/M2.00-X/VG6/-B/02B/SD-1



Note! Product picture may differ from actual product

Product No.: 97747243

The transmitter is made of 1.4404 stainless steel.

Liquid:

Liquid temperature range: -30 .. 120 °C

Technical:

Approvals: EAC
Pressure differential functionality = Yes/No: Y
Pressure relative functionality (Yes/No): N
Flow functionality (Yes/No): N
Temperature functionality (Yes/No): N
Minimum measuring pressure: 0 bar

Minimum measuring pressure: 0 bar Maximum measuring pressure: 16 bar

Installation:

Range of ambient temperature: -25 .. 60 °C

Electrical data:

Enclosure class (IEC 34-5): IP67
Length of cable: 2 m
Minimum rated voltage dc: 12.50 V
Maximum rated voltage dc: 30.00 V

Others:

Danish VVS No.: 475274516



Company name: Created by: Phone:

**Date:** 30/12/2022

Description	Value
General information:	
Product name:	DPI/0-16b/2/ C/M2.00-X/VG6/-B/02B/SD-1
Product No:	97747243
EAN number:	5710623683195
Technical:	
Approvals:	EAC
Pressure differential functionality = Yes/No:	Υ
Pressure relative functionality (Yes/No):	N
Flow functionality (Yes/No):	N
Temperature functionality (Yes/No):	N
Minimum measuring pressure:	0 bar
Maximum measuring pressure:	16 bar
Installation:	
Range of ambient temperature:	-25 60 °C
Liquid:	
Liquid temperature range:	-30 120 °C
Electrical data:	
Enclosure class (IEC 34-5):	IP67
Length of cable:	2 m
Minimum rated voltage dc:	12.50 V
Maximum rated voltage dc:	30.00 V
Others:	
Danish VVS No.:	475274516



Company name: Created by: Phone:

**Date:** 30/12/2022

## Order Data:

Position	Your pos.	Product name		Product No	Total
		DPI/0-16b/2/	1		Price on request
	1	ı	ı	1	