

**Date:** 03/11/2021

Qty. | Description

1 MAGNA3 32-100 N



Note! Product picture may differ from actual product

Product No.: On request

The Grundfos MAGNA3 circulator pump is the ideal choice for almost any building project – old or new. With its unrivalled energy efficiency, all-encompassing range and built-in communication capabilities, MAGNA3 is ideal for engineers and specifiers looking to create high-performance heating and cooling systems.

The pump is maintenance-free due to the canned-rotor type design. This also means that pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid.

MAGNA3 features an intuitive display and allows you to connect wirelessly with the Grundfos GO Remote app, giving you access to advanced reporting and monitoring.

The pump includes fieldbus communication via CIM modules as well as analog and digital inputs and configurable relays.

Control features include AUTOADAPT and FLOWADAPT. FLOWADAPT which reduces the need for throttling valves, thus cutting costs on system components.

MAGNA3 is the superior choice for a wide range of heating and cooling applications, including:

- · Mixing loops
- Heating surfaces
- · Air conditioning surfaces
- Ground-source heat pump systems
- Smaller chiller applications.

MAGNA3 is a single-phase pump and characterised by having the controller and control display integrated in the control box. The pump also has a built-in differential-pressure and temperature sensor.


The pump housing is available in both cast-iron and stainless-steel versions. The composite rotor can is carbon-fibre reinforced, the bearing plate and rotor cladding are made of stainless steel and the stator housing is made of aluminium. The power electronics are air-cooled.

MAGNA3 incorporates a 4-pole synchronous, permanent-magnet motor (PM motor). This motor type is characterised by higher efficiency than a conventional asynchronous squirrel-cage motor. The pump speed is controlled by an integrated frequency converter.



**Date:** 03/11/2021


## On request MAGNA3 32-100 N







**Date:** 03/11/2021

Description     Value       General information:     Product name:     MAGNA3 32-100 N       Product No:     On request       EAN number:     On request       Technical:     S.65 m³/h       Rated flow:     6.777 m       Head max:     100 dm       TF class:     110       Approvals on nameplate:     CE,VDE,EAC,CN ROHS,WEEE       Model:     D       Materials:       Pump benefits:
Product No: On request  EAN number: On request  Technical:  Rated flow: 5.65 m³/h  Rated head: 6.777 m  Head max: 100 dm  TF class: 110  Approvals on nameplate: CE,VDE,EAC,CN ROHS,WEEE  Model: D  Materials:
EAN number:  Technical:  Rated flow:  5.65 m³/h  Rated head: 6.777 m  Head max: 100 dm  TF class: 110  Approvals on nameplate:  Model:  D  Materials:
Technical:  Rated flow: 5.65 m³/h  Rated head: 6.777 m  Head max: 100 dm  TF class: 110  Approvals on nameplate: CE,VDE,EAC,CN ROHS,WEEE  Model: D  Materials:
Rated flow: 5.65 m³/h Rated head: 6.777 m Head max: 100 dm TF class: 110 Approvals on nameplate: CE,VDE,EAC,CN ROHS,WEEE Model: D  Materials:
Rated head:  Head max:  100 dm  TF class:  110  Approvals on nameplate:  CE,VDE,EAC,CN ROHS,WEEE  Model:  D  Materials:
Head max: 100 dm  TF class: 110 Approvals on nameplate: CE,VDE,EAC,CN ROHS,WEEE Model: D  Materials:
TF class: 110 Approvals on nameplate: CE,VDE,EAC,CN ROHS,WEEE Model: D  Materials:
Approvals on nameplate: CE,VDE,EAC,CN ROHS,WEEE Model: D  Materials:
Model: D Materials:
Materials:
Dump housing: Stainless steel
Pump housing: Stainless steel
Pump housing: EN 1.4308
Pump housing: ASTM 351 CF8
Impeller: PES 30%GF
Installation:
Range of ambient temperature: 0 40 °C
Maximum operating pressure: 10 bar
Pipe connection: G 2"
Pressure rating: PN 10
Port-to-port length: 180 mm
Liquid:
Pumped liquid: Water
Liquid temperature range: -10 110 °C
Selected liquid temperature: 60 °C
Density: 983.2 kg/m³
Electrical data:
Power input - P1: 9 171 W
Mains frequency: 50 / 60 Hz
Rated voltage: 1 x 230 V
Maximum current consumption: 0.09 1.47 A
Enclosure class (IEC 34-5): X4D
Insulation class (IEC 85):
Others:
Energy (EEI): 0.18
Net weight: 5.5 kg
Gross weight: 6.14 kg
Shipping volume: 0.015 m³
Danish VVS No.: 380796100
Swedish RSK No.: 5803242
Finnish LVI No.: 4615523
Country of origin: DE
Custom tariff no.: 84137030














**Date:** 03/11/2021

## On request MAGNA3 32-100 N








Note! All units are in [mm] unless others are stated. Disclaimer: This simplified dimensional drawing does not show all details.



**Date:** 03/11/2021

## On request MAGNA3 32-100 N



Note! All units are in [mm] unless others are stated.



**Date:** 03/11/2021

Order Data:

Product name: MAGNA3 32-100 N

Amount: 1

Product No: On request

Total: Price on request