


Position	Qty.	Description
	1	<p>CMBE 10-54 I-U-C-D-D-C</p>  <p>Product No.: 98382190</p> <p>The Grundfos CME Booster is a compact booster system for water supply in domestic applications. The integrated speed controller enables the CME Booster to keep constant pressure in the pipe system. A pressure sensor monitoring changes in the water consumption will signal to the speed controller to change the motor speed to adapt performance to the new state. The CME Booster is very easy to install. When the pipework has been installed, it is all a matter of plugging the unit into a socket, and the system is operational. The CME Booster consists of:</p> <ul style="list-style-type: none"> • CME pump with integrated frequency converter • 5-way valve • expansion tank • pressure gauge <p>Features</p> <ul style="list-style-type: none"> • Constant pressure, integrated speed control • compact • robust, stainless steel • easy installation • dry run protection <p>Thermal protection</p> <p>CME Booster pumps require no external motor protection. The MGE motor incorporates thermal protection against slow overloading and blocking (IEC 34.11: TP 211).</p> <p>Applications</p> <p>Grundfos CMBE Booster is mainly used for domestic and light commercial water supply or booster systems.</p> <p>NB:</p> <p>Suction lift: Max. 1 m, including suction-pipe pressure loss at a liquid temperature of +20 °C. (not self-priming)</p> <p>Liquid:</p> <p>Pumped liquid: Water</p> <p>Liquid temperature range: 0 .. 60 °C</p> <p>Liquid temperature during operation: 20 °C</p> <p>Density: 998.2 kg/m³</p> <p>Technical:</p> <p>Speed for pump data: 3868 rpm</p> <p>Rated flow: 12 m³/h</p>

Position	Qty.	Description
		<p>Rated head: 35.4 m</p> <p>Primary shaft seal: AVBE</p> <p>Approvals and markings: CE</p> <p>Curve tolerance: ISO9906:2012 3B</p> <p>Start pressure: Integrated Frequency converter</p> <p>Materials:</p> <p>Pump housing: Stainless steel AISI 304</p> <p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Rubber: EPDM</p> <p>Installation:</p> <p>Maximum ambient temperature: 55 °C</p> <p>Pump inlet: Rp 1 1/2</p> <p>Pump outlet: Rp 1 1/2</p> <p>Electrical data:</p> <p>Rated power - P2: 1.5 kW</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 200-240 V</p> <p>Maximum current consumption: 9,10-7,60 A</p> <p>Rated speed: 360-4000 rpm</p> <p>Enclosure class (IEC 34-5): IP55</p> <p>Insulation class (IEC 85): F</p> <p>Type of cable plug: NONE</p> <p>Mains cable: 1.5 m</p> <p>Tank:</p> <p>Tank volume: 2 l</p> <p>Others:</p> <p>Net weight: 21.8 kg</p> <p>Gross weight: 31.6 kg</p> <p>Country of origin: HU</p> <p>Custom tariff no.: 84137075</p>

Description	Value
General information:	
Product name:	CMBE 10-54 I-U-C-D-D-C
Product No:	98382190
EAN number:	5711494037926
Technical:	
Speed for pump data:	3868 rpm
Rated flow:	12 m³/h
Rated head:	35.4 m
Impellers:	2
Primary shaft seal:	AVBE
Approvals and markings:	CE
Curve tolerance:	ISO9906:2012 3B
Model:	A
Start pressure:	Integrated Frequency converter
Materials:	
Pump housing:	Stainless steel
	AISI 304
Impeller:	Stainless steel
	DIN W.-Nr. 1.4301
	AISI 304
Rubber:	EPDM
Installation:	
Maximum ambient temperature:	55 °C
Pump inlet:	Rp 1 1/2
Pump outlet:	Rp 1 1/2
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 60 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Rated power - P2:	1.5 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 200-240 V
Maximum current consumption:	9,10-7,60 A
p max system:	10 bar
Rated speed:	360-4000 rpm
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Type of cable plug:	NONE
Mains cable:	1.5 m
Tank:	
Tank volume:	2 l
Others:	
Net weight:	21.8 kg
Gross weight:	31.6 kg
Config. file no:	98442578
Country of origin:	HU
Custom tariff no.:	84137075

