





Qty.	Description																																																				
1	TPE3 50-80 S-A-F-I-BQQE-DAB  Note! Product picture may differ from actual product Product No.: On request Single-stage, close-coupled, volute pump with in-line suction and discharge ports of identical diameter. The pump is of the top-pull-out design, i.e. the power head (motor, pump head and impeller) can be removed for maintenance or service while the pump housing remains in the pipework. The shaft seal is according to EN 12756. Pipework connection is via PN 6/10 DIN flanges (EN 1092-2 and ISO 7005-2). The pump is fitted with a fan-cooled, permanent-magnet synchronous motor. The motor efficiency is classified as IE5 in accordance with IEC 60034-30-2. The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement. The pump is fitted with a combined temperature- and differential pressure sensor. Controls: <table data-bbox="204 949 639 974"> <tr> <td>Frequency converter:</td><td>Built-in</td></tr> </table> Liquid: <table data-bbox="204 1039 702 1155"> <tr> <td>Pumped liquid:</td><td>Water</td></tr> <tr> <td>Liquid temperature range:</td><td>-25 .. 120 °C</td></tr> <tr> <td>Selected liquid temperature:</td><td>20 °C</td></tr> <tr> <td>Density:</td><td>998.2 kg/m³</td></tr> </table> Technical: <table data-bbox="204 1218 817 1391"> <tr> <td>Pump speed on which pump data are based:</td><td>3000 rpm</td></tr> <tr> <td>Rated flow:</td><td>18 m³/h</td></tr> <tr> <td>Rated head:</td><td>5.8 m</td></tr> <tr> <td>Actual impeller diameter:</td><td>74 mm</td></tr> <tr> <td>Code for shaft seal:</td><td>BQQE</td></tr> <tr> <td>Curve tolerance:</td><td>ISO9906:2012 3B2</td></tr> </table> Materials: <table data-bbox="204 1456 722 1599"> <tr> <td>Pump housing:</td><td>Stainless steel EN 1.4308 ASTM CF8</td></tr> <tr> <td>Impeller:</td><td>Composite PES+30% GF</td></tr> </table> Installation: <table data-bbox="204 1664 729 1897"> <tr> <td>Range of ambient temperature:</td><td>-20 .. 50 °C</td></tr> <tr> <td>Maximum operating pressure:</td><td>10 bar</td></tr> <tr> <td>Max pressure at stated temp:</td><td>10 bar / 120 °C</td></tr> <tr> <td>Type of connection:</td><td>DIN</td></tr> <tr> <td>Size of connection:</td><td>DN 50</td></tr> <tr> <td>Pressure rating for connection:</td><td>PN 6/10</td></tr> <tr> <td>Port-to-port length:</td><td>280 mm</td></tr> <tr> <td>Flange size for motor:</td><td>56C</td></tr> </table> Electrical data: <table data-bbox="204 1962 718 2105"> <tr> <td>Motor type:</td><td>71A</td></tr> <tr> <td>IE Efficiency class:</td><td>IE5</td></tr> <tr> <td>Rated power - P2:</td><td>0.37 kW</td></tr> <tr> <td>Mains frequency:</td><td>50 / 60 Hz</td></tr> <tr> <td>Rated voltage:</td><td>1 x 200-240 V</td></tr> </table>	Frequency converter:	Built-in	Pumped liquid:	Water	Liquid temperature range:	-25 .. 120 °C	Selected liquid temperature:	20 °C	Density:	998.2 kg/m ³	Pump speed on which pump data are based:	3000 rpm	Rated flow:	18 m ³ /h	Rated head:	5.8 m	Actual impeller diameter:	74 mm	Code for shaft seal:	BQQE	Curve tolerance:	ISO9906:2012 3B2	Pump housing:	Stainless steel EN 1.4308 ASTM CF8	Impeller:	Composite PES+30% GF	Range of ambient temperature:	-20 .. 50 °C	Maximum operating pressure:	10 bar	Max pressure at stated temp:	10 bar / 120 °C	Type of connection:	DIN	Size of connection:	DN 50	Pressure rating for connection:	PN 6/10	Port-to-port length:	280 mm	Flange size for motor:	56C	Motor type:	71A	IE Efficiency class:	IE5	Rated power - P2:	0.37 kW	Mains frequency:	50 / 60 Hz	Rated voltage:	1 x 200-240 V
Frequency converter:	Built-in																																																				
Pumped liquid:	Water																																																				
Liquid temperature range:	-25 .. 120 °C																																																				
Selected liquid temperature:	20 °C																																																				
Density:	998.2 kg/m ³																																																				
Pump speed on which pump data are based:	3000 rpm																																																				
Rated flow:	18 m ³ /h																																																				
Rated head:	5.8 m																																																				
Actual impeller diameter:	74 mm																																																				
Code for shaft seal:	BQQE																																																				
Curve tolerance:	ISO9906:2012 3B2																																																				
Pump housing:	Stainless steel EN 1.4308 ASTM CF8																																																				
Impeller:	Composite PES+30% GF																																																				
Range of ambient temperature:	-20 .. 50 °C																																																				
Maximum operating pressure:	10 bar																																																				
Max pressure at stated temp:	10 bar / 120 °C																																																				
Type of connection:	DIN																																																				
Size of connection:	DN 50																																																				
Pressure rating for connection:	PN 6/10																																																				
Port-to-port length:	280 mm																																																				
Flange size for motor:	56C																																																				
Motor type:	71A																																																				
IE Efficiency class:	IE5																																																				
Rated power - P2:	0.37 kW																																																				
Mains frequency:	50 / 60 Hz																																																				
Rated voltage:	1 x 200-240 V																																																				


Qty.	Description
1	Rated current: 2.40-2.10 A Cos phi - power factor: 0.96 Rated speed: 360-4000 rpm Efficiency: 84.0% Motor efficiency at full load: 84.0 % Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F Motor No: 99137984 Others: Minimum efficiency index, MEI ≥: 0.70 Net weight: 25 kg Gross weight: 32.2 kg Shipping volume: 0.104 m³ Danish VVS No.: 382142080 Country of origin: HU Custom tariff no.: 84137051

Description	Value
General information:	
Product name:	TPE3 50-80 S-A-F-I-BQQE-DAB
Product No:	On request
EAN number:	On request
Technical:	
Pump speed on which pump data are based:	3000 rpm
Rated flow:	18 m³/h
Rated head:	5.8 m
Maximum head:	80 dm
Actual impeller diameter:	74 mm
Code for shaft seal:	BQQE
Curve tolerance:	ISO9906:2012 3B2
Pump version:	A
Materials:	
Pump housing:	Stainless steel
Pump housing:	EN 1.4308
Pump housing:	ASTM CF8
Impeller:	Composite
Impeller:	PES+30% GF
Material code:	I
Installation:	
Range of ambient temperature:	-20 .. 50 °C
Maximum operating pressure:	10 bar
Max pressure at stated temp:	10 bar / 120 °C
Type of connection:	DIN
Size of connection:	DN 50
Pressure rating for connection:	PN 6/10
Port-to-port length:	280 mm
Flange size for motor:	56C
Connect code:	F
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	71A
IE Efficiency class:	IE5
Rated power - P2:	0.37 kW
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 200-240 V
Rated current:	2.40-2.10 A
Cos phi - power factor:	0.96
Rated speed:	360-4000 rpm
Efficiency:	84.0%
Motor efficiency at full load:	84.0 %
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Built-in motor protection:	ELEC
Motor No:	99137984
Controls:	
Control panel:	HMI300 - Graphical
Function Module:	FM300 - Advanced
Frequency converter:	Built-in
Others:	
Minimum efficiency index, MEI ≥:	0.70
Net weight:	25 kg
Gross weight:	32.2 kg
Shipping volume:	0.104 m³
Config. file no:	98481397
Danish VVS No.:	382142080
Country of origin:	HU



Description	Value
Custom tariff no.:	84137051

On request TPE3 50-80 S-A-F-I-BQQE-DAB



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

Order Data:	
--------------------	--

Position	Your pos.	Product name	Amount	Product No	Total
		TPE3 50-80	1	On request	Price on request