

Company name: Created by: Phone:

Date: 08/08/2022

Qty. | Description

SP 11-5



Note! Product picture may differ from actual product

Product No.: 98699298

Submersible borehole pump, suitable for pumping clean water. Can be installed vertically or horizontally. All steel components are made in stainless steel, EN 1.4301 (AISI 304), that ensures high corrosive resistance. This pump carries drinking water approval.

The pump is fitted with a 1.1 kW MS402 motor with sand shield, lip seal, water-lubricated journal bearings and a volume compensating diaphragm. The motor is a canned type submersible motor offering good mechanical stability and high efficiency. Suitable for temperatures up to 40 °C.

The motor is not fitted with a temperature sensor. If temperature monitoring is desired, a Pt1000 sensor can be fitted.

The motor is for direct-on-line starting (DOL).

Liquid:

Pumped liquid: Water
Liquid max temp: 40 °C
Max liquid t at 0.15 m/sec: 40 °C
Selected liquid temperature: 20 °C
Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 2900 rpm

Rated flow: 11 m³/h
Rated head: 22.7 m
Shaft seal for motor: LIPSEAL
Approvals on nameplate: CE,EAC

Curve tolerance: ISO9906:2012 3B

Motor version: T40

Materials:

Pump: Stainless steel

EN 1.4301 AISI 304

Impeller: Stainless steel

EN 1.4301 AISI 304

Motor: Stainless steel

DIN W.-Nr. 1.4301

AISI 304

Installation:

Pump outlet: Rp2 Motor diameter: 4 inch

Electrical data:

Motor type: MS402 Motor type 1-phase: CSCR Rated power - P2: 1.1 kW



Company name: Created by: Phone:

Date: 08/08/2022

Qty. | Description

Power (P2) required by pump: 1.1 kW Mains frequency: 50 Hz Rated voltage: 1 x 240 V Rated current: 7.1 A Starting current: 480 % Cos phi - power factor: 0.99 Rated speed: 2860 rpm Start. method: direct-on-line

Enclosure class (IEC 34-5): IP68
Insulation class (IEC 85): B
Built-in temp. transmitter: no
Motor No: 79243105
Windings: Enamelled

Others:

Minimum efficiency index, MEI ≥: 0.60

ErP status: EuP Standalone/Prod.

Net weight:18.9 kgGross weight:20.3 kgShipping volume:0.016 m³Country of origin:GBCustom tariff no.:84137029