

Company name: Created by: Phone:

**Date:** 08/08/2022

Qty. | Description

1 SP 14-13

Product No. 1, 09600

Note! Product picture may differ from actual product

Product No.: 98699357

Submersible borehole pump, suitable for pumping clean water. Can be installed vertically or horizontally. All steel components are made in stainless steel, EN 1.4301 (AISI 304), that ensures high corrosive resistance. This pump carries drinking water approval.

The pump is fitted with a 3 kW MS4000 motor with sand shield, mechanical shaft seal, water-lubricated journal bearings and a volume compensating diaphragm. The motor is a canned type submersible motor offering good mechanical stability and high efficiency. Suitable for temperatures up to 40  $^{\circ}$ C.

The motor is not fitted with a temperature sensor. If temperature monitoring is desired, a Pt1000 sensor can be fitted.

The motor is for direct-on-line starting (DOL).

Liquid:

Pumped liquid: Water
Liquid max temp: 40 °C
Max liquid t at 0.15 m/sec: 40 °C
Selected liquid temperature: 20 °C
Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 2900 rpm

Rated flow: 14 m³/h
Rated head: 56.2 m
Shaft seal for motor: HM/CER
Approvals on nameplate: CE,EAC

Curve tolerance: ISO9906:2012 3B

Motor version: T40

Materials:

Pump: Stainless steel

EN 1.4301 AISI 304

Impeller: Stainless steel

EN 1.4301 AISI 304

Motor: Stainless steel

DIN W.-Nr. 1.4301

AISI 304

Installation:

Pump outlet: Rp2 Motor diameter: 4 inch

Electrical data:

Motor type: MS4000 Rated power - P2: 3 kW Power (P2) required by pump: 3 kW



Company name: Created by: Phone:

**Date:** 08/08/2022

## Qty. | Description

1 Mains frequency: 50 Hz

 Rated voltage:
 3 x 380-400-415 V

 Rated current:
 7.70-7.85-8.10 A

 Starting current:
 460-490-500 %

 Cos phi - power factor:
 0.82-0.77-0.73

 Rated speed:
 2850-2865-2875 rpm

Start. method: direct-on-line

Enclosure class (IEC 34-5): IP68
Insulation class (IEC 85): F
Built-in temp. transmitter: no
Motor No: 79194508
Windings: Enamelled

Others:

Minimum efficiency index, MEI ≥: 0.50

ErP status: EuP Standalone/Prod.

Net weight:32.4 kgGross weight:38 kgShipping volume:0.068 m³Danish VVS No.:388482013Finnish LVI No.:4762709Country of origin:GBCustom tariff no.:84137029