

Date: 17/06/2022

Qty. | Description

1 CUE 3X380-500V IP20 1,1KW



Note! Product picture may differ from actual product

Product No.: On request

CUE is a complete range of external frequency converters designed for speed control of a wide range of Grundfos pumps. CUE has a built-in PI controller and offers the same functionality and user-interface as Grundfos E-pumps. CUE solutions can thus be seen as an extension to the E-pump range.

By choosing a CUE-solution, you will get the following benefits:

- Grundfos E-pump functionality and user-interface
- application- and pump-family-related functions
- increased comfort compared to fixed-speed pumps
- very easy installation and commissioning compared to standard frequency converters
- speed control of pumps up to 250 kW
- speed control of pumps installed in potentially explosive environments.

CUE offers the following inputs and output:

- RS-485 GENIbus
- an analog 0-10 V input for external setpoint
- an analog 0/4-20 mA input for sensor
- four digital inputs for various functions, for instance external start/stop
- two signal relays (C/NO/NC).

Accessories:

Input/output add-on board

Provides additional input:

- one 0/4-20 mA analog input for an additional sensor
- one 0-20 mA analog output
- two inputs for Pt100/Pt1000 temperature sensors, for instance for bearing monitoring.

Motor filters:

For reduction of dU/dt and peak voltages to the motor windings and for reduction of the acoustic noise generated in the motor, a number of motor filters are offered:

- dU/dt filters , 11-250 kW
- Sine wave filters, 0.55-250 kW.

Technical:

Approvals on nameplate: CE, CULUS, C-TICK

Installation:

Range of ambient temperature: $0..50 \,^{\circ}\text{C}$ Relative humidity: $5-95 \,^{\circ}\text{M}$

Electrical data:

Rated power - P2: 1.1 kW
Mains frequency: 50 / 60 Hz

Rated voltage [V]: 3 x 380-440/441-500 V

Rated current: 3-2.7 A
Maximum current consumption: 3 A
Efficiency at full load: 96 %
Enclosure class (IEC 34-5): IP20




47/00/0000


			Date:	17/06/2022	
Qty.	Description				
	Others:				
	Others:	4.0 1			
	Net weight: Danish VVS No.:	4.9 kg 382995011			
	Danish VVS No.:	382995011			





Date: 17/06/2022


Value					
General information:					
CUE 3X380-500V IP20 1,1KW					
On request					
On request					
CE, CULUS, C-TICK					
Installation:					
0 50 °C					
5-95 %					
Wall					
1.1 kW					
50 / 60 Hz					
3 x 380-440/441-500 V					
3-2.7 A					
3 A					
96 %					
IP20					
YES					
external					
150/300 m					
4.9 kg					
382995011					















Date:

17/06/2022

On request CUE 3X380-500V IP20 1,1KW





Note! All units are in [mm] unless others are stated. Disclaimer: This simplified dimensional drawing does not show all details.



Date: 17/06/2022

Order Data:

Product name: CUE 3X380-500V IP20 1,1KW

Amount: 1

Product No: On request

Total: Price on request