


Q-Tank Booster Set



- Single / Twin Pump**
- Cat5 / AB Air Gap**
- 136L / 227L / 500L**
- Screened Overflow**
- Screened Lid Vent**
- 25mm Insulation**
- Variable Speed**
- Constant Pressure**
- Dry Run Protection**
- Self-Priming**
- Internal Pressure Vessel**
- 2-Year Guarantee**

The Trebles Q-Tank range of Cat 5 booster sets delivers quiet, efficient performance while maximising tank capacity within a compact footprint.

The Q-Tank features a variable-speed, self-priming pump mounted directly on the tank lid. This pump includes built-in controls for intelligent pressure adjustment and displays system status and alarms. Its water-cooled design eliminates the fan noise commonly associated with pumps and motors.

Constructed from fiberglass with 25mm insulation, the tank meets Category 5 / AB Air Gap regulations and includes a Screened Weir, Screened Overflow, and Screened Lid Vent. The unit also has a 3/4" Equilibrium Float Valve inlet, ensuring adequate incoming flow to meet outgoing demand in nearly all applications.


General Characteristics

		5261-136	5261-227	5261-227	5262-227	5262-500		
General	Pumps	1		2				
	Mounting	Floor Mounted						
	Dry Weight	43	52	100	62	110		
Performance	Max Pressure (m)	47						
	Max Flow (l/hr)	83			165			
Operating Conditions	Pressure Rating	8.0 Bar						
	Ambient Temperature (Max)	40°C						
	Water Temperature (Min/Max)	0°C / 35°C						
Connections	Inlet	3/4" Male BSP Equilibrium Float Valve						
	Outlet	1" Female BSP		1-1/4" Female BSP				
	Overflow	1-1/2" Female BSP						
Tank	Capacity (Nominal)	30G 136L	50G 227L	110G 500L	50G 227L	110G 500L		
	Capacity (Actual)	15G 68L	30G 140L	83G 380L	30G 140L	83G 380L		
	Fluid Category	CAT 5 / AB Air Gap						
	Other	25mm Insulation Screened Lid Vent WRAS Approved BS EN 13280:2001 RAL 7016 - Anthracite Grey						
Materials	Check Valves	AISI 304						
	Isolation Valves	CW617N UNI EN 12165						
	Fittings	AISI 304						
Electrical	Supply	230/1/50						
	Pump Power (kW)	0.65 kW			2 x 0.65 kW			
	Full Load Current (A)	2.8			5.6			

Good to know...

The Trebles Q-Tank offers a quick and simple solution for Cat 5 boosting needs. It is available in three tank sizes and includes twin pump options for the larger models.






**“You can always rely
on Trebles to give
exceptional service”**

- Steve Walters

Source: Trustpilot

Performance




Tank Fill Rate - 3/4" Equilibrium Float Valve


Inlet Pressure (Bar)	0.5	1.0	1.0	1.5	2.0	2.5	3.0	4.0	5.0
Inlet Flow (l/min)	Supply	56.8	80.5	98.7	113.7	127.3	140.9	159.1	177.3

Dimensions


5261-140







5261-227





5260-500



5262-227



5262-500



**“Excellent service
and competitive
prices”**

- Jamie Blackburn

Source: Trustpilot